


# 10K Low Rise Cantilever Pad Lift

# COATS

## 10,000 lb / 4.5T Capacity

The Coats low rise pad lift's small footprint lets you truly maximize shop space. Its drive thru design keeps the work in your shop flowing.



\*4TPD10SSR1

\*Lifting Pads in photos not included and are available for purchase separately.

## Ideal For Quick Change and Drive Thru Shops

Recommended for tire services, brakes, quick lube, and detailing. Lifts to 21.4" and collapses to 4" for a true, compact, low rise lift.



## Safety & Convenience

Made available with auto engaging mechanical locks and a mechanical lock foot release on either side

## Optional Rubber Lifting Pads

When working on vehicles with higher frames, you can protect customer vehicles by using the right sized adapters to lift without damage.



### Low Pads 1 1/2"

#4TPDB4 (Set of 4)  
#4T17106205 (Individual)



### Medium Pads 3"

#4TPDRB4 (Set of 4)  
#4T17106203 (Individual)



### Truck Pads

#4TPDTA4 (Set of 4)  
#4T47102700 (Individual)

## Durability

Rugged, twin hydraulic cylinders (4" x 22" long) and a corrosion resistant frame with powder coat finish

## Efficiency

USA-Made Bucher Pump & Motor 220v (1.5Kw)



## SPECIFICATIONS

# COATS

10K Low Rise Pad Lift	
Capacity	10,000 lbs / 4.5T
ALI Certification	Yes
Overall Dimensions (W x L)	78 1/2" x 92 1/2" (1,994mm x 2,350mm)
Deck Dimensions (W x L)	24" x 51 1/4" (610mm x 1,302mm)
Drive Over Height	4" (102mm)
Overall Lifting Height	21.4" (544mm plus adapters)
Distance Between Lifting Pads	22 3/4" (578mm)
Distance From Lift to Power Unit	127 3/4" (3,245mm)
Frame Dimensions (W x L)	52 1/2" x 78 1/2" (1,016mm x 1,816mm)
Power Supply	220V, 20 amp, 2 HP (1.5kw)
Mechanical Lock Positions	3
Lifting Time	30 seconds
Shipping Weight	866 lbs / 393 kg
Part Number	4TPD10SSR1

