

10K Low Rise Cantilever Pad Lift

10,000 lb / 4.5T Capacity

The Coats low rise pad lift's small footprint lets you truly maximize shop space. Its drive thru design keeps the work in your shop flowing.

Included Rubber Lifting Pads

When working on vehicles with higher frames, you can protect customer vehicles by using the included Low and Medium Pads to lift without damage.



#4TPD10SSR1

**INCLUDED!**

Low Pads 1 1/2"

#4TPDB4 (Set of 4)
#4T17106205 (Individual)

INCLUDED!

Medium Pads 3"

#4TPDRB4 (Set of 4)
#4T17106203 (Individual)

Ideal For Quick Change and Drive Thru Shops

Recommended for tire services, brakes, quick lube, and detailing. Lifts to 21.4" and collapses to 4" for a true, compact, low rise lift.



Safety & Convenience

Made available with auto engaging mechanical locks and a mechanical lock foot release on either side

Durability

Rugged, twin hydraulic cylinders (4" x 22" long) and a corrosion resistant frame with powder coat finish

Efficiency

USA-Made Bucher pump and motor.

Optional Truck Pads

#4TPDTA4 (Set of 4)
#4T47102700 (Individual)



10K Low Rise Pad Lift

| | |
|----------------------------------|--|
| Capacity | 10,000 lbs / 4.5 T |
| ALI Certification | Yes |
| Overall Dimensions (W x L) | 78 1/2" x 92 1/2" (1,994mm x 2,350mm) |
| Deck Dimensions (W x L) | 24" x 51 1/4" (610mm x 1,302mm) |
| Drive Over Height | 4" (102mm) |
| Overall Lifting Height | 21.4" (544mm plus adapters) |
| Distance Between Lifting Pads | 22 3/4" (578mm) |
| Distance From Lift to Power Unit | 127 3/4" (3,245mm) |
| Frame Dimensions (W x L) | 52 1/2" x 78 1/2" (1,016mm x 1,816mm) |
| Power Supply | 220V (#4TPD10SSR1) 110V (#4TPD10SSR4) |
| Mechanical Lock Positions | 3 |
| Lifting Time | 30 seconds (220V model) 50 seconds (110V model) |
| Shipping Weight | 866 lbs / 393 kg |
| Part Numbers | #4TPD10SSR1 (220V model) #4TPD10SSR4 (110V model) |

