

COATS



Maxx N²12 Two Post Lifts

High Performing 12,000 lb Two Post Lifts That Don't Quit.



Shown 4T212NSR1

Every Maxx Two Post Lift is proof-load tested by a third party at 1.5 times its rated capacity.

Power that lasts the life of the lift

Every every Maxx Two Post Lift is powered by a **USA-made** Bucher pump and motor built to deliver reliable hydraulic pressure. **It's so efficient and dependable, that keeps your shop moving for years.**

Designed to be as durable, safe, and power efficient as possible, Maxx Two Post Lifts are essential for your technicians to complete tire and under vehicle services.

12,000 lb Capacity Two Configurations

We offer our 12,000lb capacity Maxx Two Post Lifts in asymmetric and symmetric configurations.

Symmetric Lifts for Extra Stability

With a wider drive through clearance, symmetric lifts are simple to operate because the four, equally long lifting arms center the vehicle in the bay, making these lifts the most stable solution for shops that regularly lift trucks, SUVs, and other passenger vehicles with longer wheelbases.

Flexmetric Lifts: 2 Lifting Styles, 1 Lift

Flexmetric Two Post Lifts are versatile with offset adjustable arms that let techs load vehicles either symmetrically or asymmetrically—whichever the job requires. Ideal for a wide assortment of passenger cars and light trucks, asymmetric lifts don't obstruct car doors, so techs can access the vehicle interior easily for jobs that require cabin access.

Lift cars and light trucks with the right adapters

You get all the basics out of the box with every N210 Two Post Lift, including two GM Truck adapters, four double screw pad adapters, two sliding arm adapters, and eight nickel plated height adapters so you can get right to work.

Durability and Confidence you can work under

We build lifts that last longer, perform better, and cost less to operate

We spec the highest quality materials for all Maxx 2 Post Lifts. The reinforced structural components, premium USA made power units, and corrosion-resistant finishes of Maxx 2 Post Lifts are designed to last, withstand debris and corrosion, and require minimal maintenance.

Built for Safety

Every Maxx 2 Post lift is certified by the only accredited program in North America that independently verifies whether a lift complies with all industry safety and operational standards, such as structural integrity, mechanical safety systems, hydraulic and electrical systems, and load testing.



Lift Inspections by the Coats Connect Service Network

Coats Service Network Lift Inspectors are tested and qualified, to inspect ANY brand of lift, using the ALI Check360 Certified Lift Inspection Program. Be confident that your lifts have been annually certified, maintained, and inspected to meet safety and health standards.

When you choose Coats Connect to perform your annual lift inspection, you're calling upon a service network staffed coast to coast by our technicians who are supported by a central dispatch actively managing from call to completion.

Raise your expectations for quality lifts.

Be a full shop.

Lifting with Maxx Two Post Lifts is just the beginning of vehicle service. When you complete your service bays with Maxx Tire Changers and ProBalance Wheel Balancers, your entire shop standardizes on the same trusted technology. Our complete Full Shop portfolio keeps your people moving and technology turning.



The Coats Maxx Series Portfolio

The Coats Maxx portfolio - the technologies your techs need to make redundant tasks and manual processes faster and easier. The Maxx Portfolio includes single purpose technologies like tire changers and automotive lifts that do one job and do it better than any other on the market today.

For more information visit coatscompany.com

or call us at

800-688-6359



coats

USA Made Bucher Pump

The 2HP Bucher power unit is designed to keep your bay in operation. The rubber mounted unit dampens sound and prevents the motor from vibrating excessively.




Powdered Coated

Our lifts are Powder Coated and double baked to protect against structural corrosion and the harshest working environments

Bumper Guards

Carriage door bumper guards near the base of the lift columns protect the lift and prevent damage to the customer's vehicle.



Field Adjustable Height

Adjustable height options in our lift line expand the number of vehicles that can be serviced and accommodate space and ceiling height.

3 Piece Adjustable Arms

2N1 adjustable arms allow for asymmetrical and symmetrical lifting and provide longer reach and better access to hard to reach lift points.




Simple Controls

Single point release controls can be mounted on either side at time of install to align with shop layout. Comes with document holder and ALL materials.

Heavy Duty Pulleys

Self lubricating bronze bushings and large diameter cables reduce maintenance costs (4.5" pulleys and 3/8" cables)



Stronger Arm Restraints

Reinforced carriage arm pin holes and plated gear style arm restraints make the lift arms last longer and sag less.

Optional Accessories

85607986	Round Double Screw
85009048	EV Adapter Set
4T2PEV4	Low Profile EV Arm Adapters (Set of 4)
4T2PRBEV	EV Rubber Block Adapters (Set of 4)
4TAEPS	Air Electric Station with Tool Holder

Included Accessories



Double Screw Pad Adapter (Set of 4)
#4T42100042



3" and 6" Nickel Plated Height Adapter Set (Set of 8 pcs)
#4T2PTA36



Sliding Arm Adapters (Set of 2)
#4T2PHA



GM 7" Frame Adapter (Set of 2)
#4TGMTA



For more information visit coatscompany.com, scan the QR code, or call us at 800-688-6359

coats

	N ² 12 (Flexmetric)	N ² 12S (Symmetric)
Capacity	12,000 lb/5.5T	12,000 lb/5.5T
A Overall Height	158 7/8" (4,035mm)	154 7/8" (3,934mm)
B Overall Width	137 1/2" (3,483 mm)	145 1/8" (3,66mm)
C Width Between Columns	109 3/4" (2,788mm)	117 3/4" (2,991mm)
D Drive Thru Width	89 1/8" (2,264mm)	105 5/8" (2,682mm)
E Under Bar Clearance	153 1/2" (3,899mm)	149 1/2" (3,797mm)
F Lowered Height (standard pad fully in)	3 3/4" (102mm)	3 3/4" (102mm)
G Raised Height (standard pad fully out)	77" (1,958mm)	77" (1,958mm)
H Raised Height (with extensions)	86" (2,184mm)	86" (2,184mm)
I Front Arm Reach	19 3/8"-42" (492mm-1,067mm)	36 1/4"-61 5/8" (921mm-1,565mm)
J Rear Arm Reach	36 1/4"-61 5/8" (921mm-1,565mm)	36 1/4"-61 5/8" (921mm-1,565mm)
Lifting Time	75 seconds	75 seconds
Standard Power Requirements	230V, 1PH, 60Hz, 20A	230V, 1PH, 60Hz, 20A
*Optional Field Adjustable Height at Install	A: 154 7/8"	A: 157 7/8" and B: 137 1/8"
ALI Certified	Yes (see part numbers)	Yes (see part numbers)
Part Numbers	4T212NSR1 (Red) 4T212NSB1 (Blue)	4T212SSR1 (Red) 4T212SSB1 (Blue)

Warranty: 1 year parts, 6 months labor
1 year freight on all parts

* Not recommended set-up, only use when there is clearance issues during install. Dimensions C, D, E change accordingly.

